

International application No. PCT/FI 00/00804

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B02C 7/00, D21D 1/30
According to International Patent Classification (IPC)
According to IPC
According to

Minimum documentation searched (classification system followed by classification symbols)

TPC7 - RO2C D21R D21D

SE,DK,	FI,NO classes as above		
Electronic d	ata base consulted during the international search (nam	e of data base and, where practicable, searc	h terms used)
C. DOCU	MENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No
A	SE 441758 B (SUNDS DEFIBRATOR A (04.11.85), page 1, line 36 figure 1	B), 4 November 1985 - page 2, line 11,	1,8
A	EP 0931584 A1 (VOITH SULZER PAP GMBH), 28 July 1999 (28.07.9 line 5 - line 37, figure 1	IERTECHNIK PATENT 99), column 3,	1,8
,			
 Furthe	er documents are listed in the continuation of Box	C. X See patent family annex	ς.
documer to be of earlier a filing dat documen cited to o	tategories of cited documents at defining the general state of the art which is not considered particular relevance pplication or patent but published on or after the international te at which may throw doubts on priority claim(s) or which is establish the publication date of another citation or other eason (as specified) at referring to an oral disclosure, use, exhibition or other	"I later document published after the inti- date and not in conflict with the appli- the principle or theory underlying the "X" document of particular relevance: the considered novel or cannot be conside- step when the document is taken alone "Y" document of particular relevance: the considered to involve an inventive step	cation but cited to understand invention claimed invention cannot he red to involve an inventive : claimed invention cannot he

0 9 -01- 2001 27 December 2000 Name and mailing address of the ISA Authorized officer Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Wiva Asplund/ELY Facsimile No. +46 8 666 02 86 Telephone No. +46 8 782 25 00 Form PCT/ISA/210 (second sheet) (July 1998)



International application No. PCT/FI 00/00804

04/12/00

	nt document search report		Publication date		Patent family member(s)	Publication date
SE	441758	В	04/11/85	AU	3934985 A	01/11/85
				DE	207937 T	30/04/87
				EP	0207937 A	14/01/87
				FI	863998 A	02/10/86
				JP	61501715 T	14/08/86
				NO	854832 A	02/12/85
				NZ	211324 A	11/07/86
				SE	8401846 D	00/00/00
				WO	8504433 A	10/10/85
EP	0931584	A1	28/07/99	DE	19802260 A	29/07/99



PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference		S. Marc	
BP100192/MAK/PKK	FOR FURTHER ACTION		ation of Transmittal of International v Examination Report (Form PCT/IPEA/416)
International application No.	International filing date (day)		Priority date (day/month/year)
PCT/F100/00804	21.09.2000	•	21.09.1999
International Patent Classification (IPC) on B 02 C 7/00, D 21 D 1		C7	
Applicant		·	· · · · · · · · · · · · · · · · · · ·
VALMET MECHANICAL PUL	PING OY et al		
been amended and are the ba	of 4 sheets, inch	36. Iding this cover of the description containing rect	sheet. on, claims and/or drawings which have
These annexes consist of a total of			
3. This report contains indications rel	ating to the following items:		
I Basis of the report			
II Priority			
	animian with maned to manale.	•	
<u>==</u>	opinion with regard to novelty,	inventive step a	and industrial applicability
IV Lack of unity of inven			
V Reasoned statement un citations and explanati	nder Article 35(2) with regard to ions supporting such statement	o novelty, inven	tive step or industrial applicability;
VI Certain documents cite	≭d		
VII Certain defects in the i	international application		•
VIII Certain observations of	n the international application		
	-		
Description (all)			
Date of submission of the demand	Date of	of completion of	this report
19.04.2001	04.	09.2001	
Name and mailing address of the IPEA/SE	Autho	rized officer	
Patent- och registreringsverket Box 5055	Telex 17978		Į.
S-102 42 STOCKHOLM	PATOREG-S Wiv	a Asplun	
Facsimile No. 08-667 72 88		ione No. 08-7	

Form PCT/IPEA/409 (cover sheet) (January 1998)



International application No.
PCT/FI00/00804

I. Ba	asis of the report		
1. Wit	th regard to the elements of the international application:*		
\boxtimes	7		
	the description:		
!	pages		, as originally filed
	pages		, as originally med , filed with the demand
	pages		
	the claims:		
	pages		, as originally filed
	pages	, as amended (together with any s	statement) under article 19
	pages		_ , filed with the demand
_	pages	, filed with the letter of	
لــا	the drawings:		•
	pages		, as originally filed
	pages		, filed with the demand
	the sequence licting part of the description	, filed with the letter of	
لبا	the sequence listing part of the description: pages		
			, as originally filed
	pages		_ , filed with the demand
	the language of a translation furnished for the purposes of inte the language of publication of the international application (ur the language of the translation furnished for the purposes of in or 55.3).	under Rule 48.3(b)). International preliminary examination	a (under Rules 55.2 and/
3. With prelin	regard to any nucleotide and/or amino acid sequence disclose ninary examination was carried out on the basis of the sequence contained in the international application in written form. filed together with the international application in computer refurnished subsequently to this Authority is a writer.	e listing:	e international
H	furnished subsequently to this Authority in written form.		
	furnished subsequently to this Authority in computer readable. The statement that the subsequently furnished written sequence international application as filed has been furnished. The statement that the information recorded in computer readabeen furnished.	ce listing does not go beyond the discl	
4.	The amendments have resulted in the cancellation of:		
	the description, pages	•	
		%	
	the claims, Nos. the drawings, sheet/fig		
5.	This report has been established as if (some of) the amendment beyond the disclosure as filed, as indicated in the Supplemental	its had not been made, since they have al Box (Rule 70.2 (c)).**	e been considered to go
* Repla	acement sheets which have been furnished to the receiving Office s report as "originally filed" and are annexed to this report sing	ca in rasponsa to an impitation and an	Article 14 are referred to Rules 70.16
unu /	0.17). eplacement sheet containing such amendments must be referred		

International application No.

PCT/FI00/00804

V.	Reasoned statement under Articl citations and explanations suppor		egard to novelty, inventive step or industrial applicability; tement	
ı.	Statement			
	Novelty (N)	Claims Claims	1-12	- YES
		Claims		140
	Inventive step (IS)	Claims Claims	1-12	- YES
				
	Industrial applicability (IA)	Claims Claims	1-12	YES NO

2. Citations and explanations (Rule 70.7)

The documents cited in the International Search Report represent the prior art. The claimed invention stated in claims 1-12 is not considered to be anticipated by these documents. None of the documents or any relevant combination of them reveal a method or a device for dispersing pulp with a running wheel acting as pump arranged at the outlet end of a narrow opening between conical surfaces, where the dispersing event takes place as described by these claims.

According to the arguments stated above, the invention claimed in claim 1-12 is novel, considered to involve an inventive step and have industrial applicability.



PATENT COOPERATION REATY

From the INTERNATIONAL BUREAU

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

o	:		

Commissioner
US Department of Commerce
United States Patent and Trademark
Office, PCT
2011 South Clark Place Room
CP2/5C24
Arlington, VA 22202
FTATS-UNIS D'AMERIQUE

Date of mailing (day/month/year) 23 May 2001 (23.05.01)	ETATS-UNIS D'AMERIQUE in its capacity as elected Office
International application No. PCT/FI00/00804	Applicant's or agent's file reference BP100192
International filing date (day/month/year) 21 September 2000 (21.09.00)	Priority date (day/month/year) 21 September 1999 (21.09.99)
Applicant	
KANKAANPÄÄ, Veikko	

1.	The designated Office is hereby notified of its election made:
	X in the demand filed with the International Preliminary Examining Authority on:
	19 April 2001 (19.04.01)
	in a notice effecting later election filed with the International Bureau on:
2.	The election X was
	was not
	made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland

Authorized officer

Claudio Borton

Facsimile No.: (41-22) 740.14.35

Telephone No.: (41-22) 338.83.38



	From the INTERNATIONAL BUREAU
PCT	То:
NOTIFICATION OF THE RECORDING OF A CHANGE (PCT Rule 92bis.1 and Administrative Instructions, Section 422) Date of mailing (day/month/year) 18 févrior 2002 (18 02 02)	BERGGREN OY AB P.O. Box 16 FIN-00101 Helsinki FINLANDE
18 février 2002 (18.02.02)	
Applicant's or agent's file reference BP100192	IMPORTANT NOTIFICATION
International application No. PCT/FI00/00804	International filing date (day/month/year) 21 septembre 2000 (21.09.00)
The following indications appeared on record concerning: The applicant the inventor	the agent the common representative
Name and Address VALMET MECHANICAL PULPING OY P.O. Box 125 FIN-37601 Valkeakoski Finland	State of Nationality State of Residence FI FI Telephone No.
	Facsimile No. Teleprinter No.
2. The International Bureau hereby notifies the applicant that the X the person the name X the add	[
Name and Address METSO PAPER, INC. Fabianinkatu 9 A	State of Nationality State of Residence FI FI
FIN-00130 Helsinki Finland	Telephone No.
, mana	Facsimile No.
	Teleprinter No.
3. Further observations, if necessary:	•
4. A copy of this notification has been sent to:	
X the receiving Office	the designated Offices concerned
the International Searching Authority the International Preliminary Examining Authority	X the elected Offices concerned other:
T	
The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland	Authorized officer Anne KARKACHI
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38



Original (for SUBMISSION) - printed on 21.09.2000 12:17:54 PM

0	For receiving Office use only	DOT/TI 0 2 0 0 0 1 1
0-1	International Application No.	PCT/Fl 0 0 / 0 0 0 0 4
0-2	International Filing Date	2 1 SEP 2000 (2 1 -09- 2000)
0-3	Name of receiving Office and "PCT International Application"	The Finnish Patent Office PCT International Application
0-4	Form - PCT/RO/101 PCT Request	
0-4-1	Prepared using	PCT-EASY Version 2.91 (updated 01.07.2000)
0-5	Petition The undersigned requests that the present international application be processed according to the Patent Cooperation Treaty	
0-6	Receiving Office (specified by the applicant)	National Board of Patents and Registration (Finland) (RO/FI)
0-7	Applicant's or agent's file reference	BP100192
1	Title of invention	METHOD AND DEVICE FOR PROCESSING PULP
11	Applicant	
11-1	This person is:	applicant only
11-2	Applicant for	all designated States except US
11-4	Name	VALMET MECHANICAL PULPING OY
II-5	Address:	P.O. Box 125
		FIN-37601 Valkeakoski
		Finland
II-6	State of nationality	FI
II-7	State of residence	FI
111-1	Applicant and/or inventor	
III-1-1	This person is:	applicant and inventor
III-1-2	Applicant for	US only
III-1-4	Name (LAST, First)	KANKAANPÄÄ, Veikko
III-1-5	Address:	Rengastie 24 B
		FIN-37600 Valkeakoski
		Finland
III-1-6	State of nationality	FI
III-1-7	State of residence	FI



BP100192

Original (for SUBMISSION) - printed on 21.09.2000 12:17:54 PM

IV-1	Agent or common representative; or address for correspondence The person identified below is hereby/has been appointed to act on behalf of the applicant(s) before the competent International Authorities as:	agent			
IV-1-1	Name	BERGGREN OY AB			
IV-1-2	Address:	P.O. Box 16			
	7.00.000.				
		FIN-00101 Helsinki			
IV-1-3	Telephone No.	Finland			
IV-1-3	Facsimile No.	+358-9-693701			
		+358-9-6933944			
IV-1-5	e-mail	email.box@berggren.fi			
V V-1	Designation of States Regional Patent				
V -1	(other kinds of protection or treatment, if any, are specified between parentheses	and any other State which is a			
	after the designation(s) concerned)	Contracting State of the Harare Protocol			
		and of the PCT			
		EA: AM AZ BY KG KZ MD RU TJ TM and any			
		other State which is a Contracting State			
		of the Eurasian Patent Convention and of			
		the PCT			
		EP: AT BE CH&LI CY DE DK ES FI FR GB GR			
	1	IE IT LU MC NL PT SE and any other State			
	İ	which is a Contracting State of the			
]	European Patent Convention and of the			
		PCT			
		OA: BF BJ CF CG CI CM GA GN GW ML MR NE			
		SN TD TG and any other State which is a			
		member State of OAPI and a Contracting			
		State of the PCT			
V-2	National Patent (other kinds of protection or treatment, if	AE AG AL AM AT AU AZ BA BB BG BR BY BZ			
	any, are specified between parentheses	CA CH&LI CN CR CU CZ DE DK DM DZ EE ES			
	after the designation(s) concerned)	FI GB GD GE GH GM HR HU ID IL IN IS JP			
		KE KG KP KR KZ LC LK LR LS LT LU LV MA			
		MD MG MK MN MW MX MZ NO NZ PL PT RO RU			
		SD SE SG SI SK SL TJ TM TR TT TZ UA UG			
		US UZ VN YU ZA ZW			
V-5	Precautionary Designation Statement				
	In addition to the designations made under items V-1, V-2 and V-3, the				
	applicant also makes under Rule 4.9(b)				
	all designations which would be permitted under the PCT except any				
	designation(s) of the State(s) indicated				
	under item V-6 below. The applicant				
	declares that those additional designations are subject to confirmation				
	and that any designation which is not				
	confirmed before the expiration of 15 months from the priority date is to be				
	regarded as withdrawn by the applicant				
V-6	at the expiration of that time limit. Exclusion(s) from precautionary	· · · · · · · · · · · · · · · · · · ·			
	designations	NONE			

PCT REQUEST


BP100192

Original (for SUBMISSION) - printed on 21.09.2000 12:17:54 PM

VI-1	Priority claim of earlier national		
	application		
VI-1-1	Filing date	21 September 1999 (2	1.09.1999)
VI-1-2	Number	19992010	
VI-1-3	Country	FI	
VI-2	Priority document request		
	The receiving Office is requested to prepare and transmit to the International Bureau a certified copy of the earlier application(s) identified above as item(s):	VI-1	
/II-1	International Searching Authority Chosen	Swedish Patent Offic	e (ISA/SE)
/111	Check list	number of sheets	electronic file(s) attached
/III-1	Request	4	-
/III-2	Description	5	-
/111-3	Claims	2	-
/111-4	Abstract	1	bp100192.txt
/111-5	Drawings	1	-
/111-7	TOTAL	13	
	Accompanying items	paper document(s) attached	electronic file(s) attached
/III-8	Fee calculation sheet	✓	-
/III-9	Separate signed power of attorney	✓	-
/III-16	PCT-EASY diskette		diskette
/111-17	Other (specified):	Copy of Official	-
		Action in FI	
		19992010	
/III-18	Figure of the drawings which should accompany the abstract	1	
/III-19	Language of filing of the international application	Finnish	
X-1	Signature of applicant or agent	2-2-	
X-1-1	Name	BERGGREN OY AB	
X-1-2	Name of signatory	Juhani Kupiainen	
X-1-3	Capacity	Patent Attorney	

FOR RECEIVING OFFICE USE ONLY

10-1	Date of actual receipt of the purported international application	2 1 SEP 2000	(2 1 -09- 2000)
10-2	Drawings:		· · · · · · · · · · · · · · · · · · ·
10-2-1	Received		
10-2-2	Not received		
10-3	Corrected date of actual receipt due to later but timely received papers or drawings completing the purported international application		
10-4	Date of timely receipt of the required corrections under PCT Article 11(2)		
10-5	International Searching Authority	ISA/SE	
10-6	Transmittal of search copy delayed until search fee is paid		



4/4

PCT REQUEST

BP100192

Original (for SUBMISSION) - printed on 21.09.2000 12:17:54 PM

FOR INTERNATIONAL BUREAU USE ONLY

11-1 Date of receipt of the record copy by the International Bureau	0 6 OCTOBER 2000	. i v. 10, 00)
---	------------------	-----------------




Fig.1




Fig.2




Fig. 3



Menetelmä ja laite puukuitumassan käsittelemiseksi

5

30

Tämän keksinnön kohteena on menetelmä puukuitumassan, etenkin jäte- tai keräyspaperia sisältävän massan, joka sisältää kiintoaineksen ja nestefaasin, dispergoimiseksi, jossa hienonnettu massa syötetään toistensa suhteen pyörimisliikkeeseen saatettujen dispergaattorin teräpintojen väliin. Keksinnön kohteena on myös dispergaattori mainitun menetelmän soveltamiseksi.

Puukuitumassaa käsitellään dispergaattorissa, jossa massan epäpuhtaudet erottuvat kuiduista, kuitujen kuitenkaan vaurioitumatta käsittelyssä. Tämä on mahdollista dispergaattorin keskinäisesti vastakkaisten terillä varustettujen teräpintojen avulla, joista toinen teräpinta alustoineen (staattori) on kiinteä ja toinen teräpinta alustoineen (roottori) pyörii toisen suhteen. Terät ja niiden väliin jäävät raot saavat aikaan massan edestakaisen liikkeen dispergaattorissa, jolloin epäpuhtauksien erottuminen kuiduista tapahtuu. Dispergoinnin tarkoituksena on tavallisesti mekaanisesti irrottaa epäpuhtaudet kuiduista ja samalla jauhaa epäpuhtaudet pienemmiksi partikkeleiksi vaikuttamatta kuitenkaan negatiivisesti kuitujen ominaisuuksiin.

Dispergaattori sopii erityisesti mustepartikkeleja tai epäpuhtauksia, kuten liimoja ja sulapinnoitteita, sisältävän jäte- tai keräyspaperia sisältävän massan käsittelemiseen. Tällaisen massan käsittelyyn tarkoitettu menetelmä ja hajotin on esitetty SE-patenttijulkaisussa 502 906. Julkaisussa esitetään jauhatuselementti, joka koostuu kahdesta vastakkaisesta jauhinkiekosta, jotka on varustettu kohohammaskuvioilla. Kaltevat kohokuviot on sijoitettu kiekoille säteensuuntaisesti.

Tasomaisten dispergaattoreiden lisäksi voidaan käyttää kartiomallisia dispergaattoreita. Kartiodispergaattoreiden ongelmana on kuitenkin niiden suoma vähäinen massan siirtovoima. Tästä johtuen kun poistokammion paine on suuri, eli hammastusten välisessä raossa työntövoima on suuri, työstöpintojen säätö vaikeutuu ja dispergaattorin kuormitus lisääntyy. Dispergaattori või jopa tukkeutua, jolloin prosessi keskeytyy. Tämä ongelma vältetään käyttämällä keksinnön mukaista menetelmää.

Keksinnön kohteena olevassa menetelmässä puukuitumassan, etenkin jäte- tai ke-35 räyspaperia sisältävän massan, dispergointi tapahtuu kartiopintojen välisessä teräraossa, jonka poistopäähän on järjestetty pumppuna toimiva juoksupyörä, jolla massa pumpataan keskipakovoiman avulla dispergaattorista ulos. Keksinnön mukaisessa menetelmässä käytetään kartiodispergaattoria, jonka etuna on laaja työstöalue. Tällöin ulompi kartio toimii edullisesti staattorina ja sisempi edullisesti roottorina, johon on lisäksi kiinnitetty juoksupyörä. Juoksupyörä on kiinnitetty sopivimmin roottorina toimivaan kartioon siten, että se kääntää massan virtausta poispäin kartion akselista. Edullisimmin juoksupyörä on kohtisuorassa kartion akseliin nähden niin, että virtaus tapahtuu aksiaalisesti kohtisuorassa tasossa. Etuna tasomaiseen dispergaattoriin nähden kartiodispergaattorilla on se, että teräpinta-alaa voidaan nostaa 50-150 % suhteessa tasomaiseen dispergaattoriin, jolloin terän ja epäpuhtauden välisen kohtaamisen todennäköisyys nousee huomattavasti ja dispergointitehokkuus paranee.

5

10

15

20

Keksinnön mukaisessa menetelmässä dispergaattorin teräpintojen toimintaa on mahdollista säätää ja ohjata laskemalla dispergaattorin poistoalueen painetta eli poistopainetta. Dispergaattorin poistopaine on mahdollista saattaa alhaisemmaksi kuin dispergaattorin poistokammion paine liittämällä dispergaattorin roottoriin juoksupyörä. Poistopaine on mahdollista laskea niin alhaiseksi, että teräalueen loppupäässä on alhaisempi paine kuin alkupäässä, jolloin syntyy imu loppupäätä kohden, jolloin vältytään ongelmilta, jotka aiheutuvat perinteisen kartiodispergaattorin siirtovoiman vähäisyydestä. Keksinnön mukaisessa menetelmässä mahdollisuus dispergaattorin tukkeutumiseen on siten vähäinen. Tästä seuraa myös, että keksinnön mukaisessa menetelmässä dispergaattorin työstöpintojen teriä voidaan asentaa tiheämpään, jolloin terien määrä kasvaa, jolloin edelleen dispergoinnin tehokkuus ja tuottavuus paranevat.

Keksinnön mukaisessa menetelmässä teräalueen syöttöpään paine eli syöttöpaine voi olla huomattavastikin alhaisempi kuin paine dispergaattorin poistokammiossa, johon juoksupyörä pumppaa massan. Tällöin poistokammion paine voidaan saattaa niin korkeaksi että dispergoitu massa voidaan siirtää putkiston läpi ja dispergaattoria korkeammallekin tasolle ilman erillistä pumppua. Tällä tavoin keksinnön mukaisella menetelmällä voidaan korvata menetelmä, jossa käytetään yhdistelmää dispergaattori, pumppu, pumpun syöttötankki ja joissakin tapauksissa ruuvikuljetin. Edelleen keksinnön mukaisella menetelmällä saavutetaan dispergaattorin hyvä tehokkuus ja tuottavuus, massan siirto prosessin seuraavaan vaiheeseen sekä tarvittaessa prosessin seuraavalle vaiheelle riittävä massan hydrostaattinen paine. Keksinnön mukainen menetelmä kuluttaa siis vähemmän energiaa kuin perinteiset menetelmät.

Hydrostaattinen paine massan pumppaamiseksi edelleen seuraavaan putkistoon voidaan tuottaa dispergaattorilla tai erillisellä pumppulaitteistolla. Dispergaattorin

poistoalueen pumppaus suoritetaan teräraon poistopäähän sijoitetulla juoksupyörällä, joita voi olla laitteessa useampia. Menetelmässä dispergointi ja pumppaus suoritetaan siis laitteen eri osissa, jolloin ne eivät haittaa toisiaan.

Keksinnön mukaisessa menetelmässä voidaan lisäksi laimentaa massa teräraon poistopäässä juoksupyörän imupuolelle syötetyn nesteen avulla. Näin massa voidaan tarvittaessa laimentaa seuraavaa prosessia varten ilman erillistä työvaihetta. Poistokammiossa on riittävä sekoitus tehokkaan laimennuksen suorittamiseksi ilman erillistä sekoituslaitetta. Tarvittava laimennusneste, joka voi olla paineistettua tai ei, syötetään juoksupyörän imupuolelle syöttökanavan kautta, joita on laitteessa vähintään yksi.

Keksinnön kohteena on edelleen dispergaattori puukuitumassan, etenkin jäte- tai keräyspaperia sisältävän massan, joka sisältää kiintoaineksen ja nestefaasin, dispergoimiseksi. Keksinnön mukainen dispergaattori käsittää terillä varustetut vastakkaiset kartiopinnat, jotka ovat saatettavissa pyörimisliikkeeseen toistensa suhteen, syöttökanavan massan johtamiseksi kiertopintojen väliseen terärakoon sekä poistokammion dispergoidun massan poistamiseksi. Dispergaattorille on tunnusomaista se, että sen teräpinnat ovat kartiomaiset ja että se käsittää lisäksi teräraon poistopäähän sijoitetun juoksupyörän.

Kuten edellä on todettu, keksinnön mukaan dispergaattorina käytetään kartiodispergaattoria, jonka etuna on laaja työstöalue. Tällöin ulompi kartio toimii edullisesti staattorina ja sisempi roottorina, johon on lisäksi kiinnitetty juoksupyörä. Juoksupyörä on kiinnitetty roottorina toimivaan kartioon sopivimmin siten, että se kääntää massan virtausta poispäin kartion akselista. Etuna tasomaiseen dispergaattoriin nähden kartiodispergaattorilla on se, että terien määrää voidaan nostaa 50-150 % suhteessa tasomaiseen dispergaattoriin jolloin terän ja epäpuhtauden välisen kohtaamisen todennäköisyys nousee huomattavasti ja dispergointitehokkuus paranee.

30

35

15

20

25

Kartiodispergaattorilla saavutetaan edelleen edellä mainittujen lisäksi mm. seuraavia etuja: epäpuhtauksien dispergoinnissa saavutetaan samalla tunnetulla energiatasolla korkeampi tehokkuus kuin tasomaisella dispergaattorilla; massan kuitujen katkeilu vähenee, koska energia jakaantuu suuremmalle määrälle teriä, jolloin voidaan käyttää suurempaa energiaa kuin tasomaisella dispergaattorilla, kuitujen kuitenkaan vahingoittumatta; dispergaattorin terien käyttöikä pitenee, koska työstöpinta-ala on laajempi ja energia/terä on alhaisempi.

Kartiodispergaattorin teräpinnat voivat olla 10-75° kulmassa kartion akseliin nähden, edullisesti 10-30° kulmassa kartion akseliin nähden. Teräpinnat voivat muodostua myös toistensa jatkeena olevista lieriö- ja kartiopinnoista, mutta terät sijaitsevat edullisesti pääasiassa kartiopinnoilla. Terät on sijoitettu liikkuvalle teräpinnalle (roottori) ja kiinteälle teräpinnalle (staattori) siten, että terät asettuvat limittäin. Terien muoto on vapaasti valittavissa, mutta niiden koon tulee olla sellainen, että roottori ja staattori muodostavat parin, jossa terät asettuvat limittäin.

Juoksupyörän virtauskanavat on suunniteltu siten, että paine kasvaa juoksupyörän ulkokehää kohden mentäessä (vrt. keskipakopumppu). Korkea paine virtauskanavissa ja niiden poistoaukoissa estää massan takaisinvirtauksen poistokammiosta teräalueelle. Juoksupyörän ja poistokammion seinämän välissä on rako, joka mahdollistaa juoksupyörän vapaan liikkumisen, mutta ei massan takaisinvirtausta tai paineen alentumista poistokammiossa.

Keksintöä selostetaan seuraavassa yksityiskohtaisemmin viittamalla oheisiin piirustuksiin, joissa:

- kuvio 1 esittää erästä keksinnön mukaisen dispergaattorin sovellutusmuotoa,
- 20 kuvio 1 on osittainen pitkittäisleikkaus kyseisestä dispergaattorista,

5

10

15

30

- kuvio 2 esittää osakaaviota kuviossa 1 esitetyn dispergaattorin juoksupyörän rakenteesta ja virtauskanavista. Kuviossa on lisäksi esitetty juoksupyörän virtauskanavien toimintaperiaate. Osakaavio on poikkileikkaus kuvioon 1 merkitystä kohdasta AA, ja
- 25 kuviossa 3 esitetään kuvion 1 mukaisen dispergaattorin teräpinnan rakennetta.

Kuviossa 1 esitetty kartiodispergaattori koostuu runko-osasta, kartiosta, johon kuuluvat kartiopinnat, juoksupyörästä ja poistokammiosta. Kuvion 1 osat ovat: 1 syöttöpiste; 2 kartio; 3 kartiopinnat; 4 terä; 5 terärako; 6 poistopiste; 7 juoksupyörä; 8 juoksupyörän virtauskanava; 9 poistokammio; 10 laimennusnesteen syöttökanava; 11 rako.

Puukuitumassa, joka sisältää jäte- tai keräyspaperia ja jonka sakeus on sopivasti 15-35 %, syötetään kartiodispergaattoriin syöttöpisteessä 1. Massa liikkuu kartiopinnoilla 3 terien 4 välisissä raoissa 5 edestakaisin siirtyen samalla eteenpäin kartiolla 2. Teräalueen poistopisteessä 6 syntyvä alipaine lisää massan liikkuvuutta eteenpäin kohti poistopistettä 6. Teräalueella kuitumassan epäpuhtaudet erottuvat mekaanisesti massan kuiduista, lisäksi epäpuhtaudet jauhautuvat pienemmiksi partikkeleiksi.

Massan siirtyessä teräalueen poistopisteeseen 6 se sekoittuu laimennusnesteeseen, joka syötetään poistopisteeseen 6 laimennusnesteen syöttökanavan 10 kautta. Laimennusneste voi olla paineistettua tai ei. Juoksupyörän 7 pyöriessä syntyy virtaus, jolloin massa sekoittuu laimennusnesteeseen. Pyörimisliike myös aikaansaa edellä esitetyt paine-erot laitteen eri osien välillä. Laimennettu massa siirtyy juoksupyörän virtauskanavien 8 kautta kuviossa 2 esitetyn periaatteen mukaisesti poistokammioon 9. Poistokammiossa 9 massan sakeus on sopivasti 4-12 %.

5

10

15

20

25

Kuviossa 2 on esitetty osakaavio juoksupyörän 7 ja virtauskanavien 8 rakenteesta sekä juoksupyörän virtauskanavien 8 toimintaperiaate. Osakaavio on poikkileikkaus kuvioon 1 merkitystä kohdasta AA. Juoksupyörässä 7 on aksiaalisesti ulospäin johtavat virtauskanavat 8, joita rajaavat elimet 12. Massan virtaus 13 tapahtuu juoksupyörän 7 akselista poispäin juoksupyörän 7 pyörimissuunnan 14 vastaiseen suuntaan. Juoksupyörä 7 on kiinnitetty roottoriin siten, että massan virtauksen 13 suunta muuttuu kartion akseliin nähden.

Juoksupyörän 7 ja poistokammion 9 seinämän välissä on rako 11, joka mahdollistaa juoksupyörän 7 vapaan liikkumisen, mutta ei massan takaisinvirtausta tai paineen alentumista poistokammiossa.

Kuviossa 3 on esitetty terien 4 sijoittelu kartiopinnalla 3. Terät voivat olla kartiovaippaviivojen suuntaisia tai määrätyssä kulmassa niihin nähden ja niiden muotoa ja etäisyyttä toisistaan voidaan vapaasti vaihdella samoin kuin eri vyöhykkeiden teräkuvioita.

Alan ammattimiehelle on selvää, että keksinnön mukainen menetelmä ja laite puukuitumassan dispergoimiseksi ei rajoitu edellä esitettyyn esimerkkiin vaan perustuu seuraaviin patenttivaatimuksiin.



Patenttivaatimukset

1. Menetelmä puukuitumassan, etenkin keräyspaperia sisältävän massan, joka sisältää kiintoaineksen ja nestefaasin, dispergoimiseksi, jossa menetelmässä hienonnettu massa syötetään toistensa suhteen pyörimisliikkeeseen saatettujen dispergaattorin teräpintojen (3) väliin, tunnettu siitä, että dispergointi tapahtuu kartiopintojen (3) välisessä teräraossa (5), jonka poistopäähän (6) on järjestetty pumppuna toimiva juoksupyörä (7), jolla massa pumpataan keskipakovoiman avulla dispergaattorista ulos.

10

20

- 2. Patenttivaatimuksen 1 mukainen menetelmä, tunnettu siitä, että dispergaattorin sisempi kartio toimii roottorina ja ulompi kartio toimii staattorina.
- 3. Jonkin edellisistä patenttivaatimuksista mukainen menetelmä, tunnettu siitä, että mainittu juoksupyörä (7) on kiinnitetty roottorina toimivaan kartioon siten, että se kääntää massan virtausta poispäin kartion akselista.
 - 4. Jonkin edellisistä patenttivaatimuksista mukainen menetelmä, tunnettu siitä, että massan laimennus teräraon (5) poistopäässä (6) suoritetaan juoksupyörän (7) imupuolelle syötetyllä nesteellä.
 - 5. Patenttivaatimuksen 4 mukainen menetelmä, tunnettu siitä, että dispergoitavan massan sakeus ennen laimennusta on 15-35 %.
- 25 6. Patenttivaatimuksen 4 tai 5 mukainen menetelmä, tunnettu siitä, että laimennuksen jälkeen massan sakeus on 4-12 %.
- 7. Jonkin edellisistä patenttivaatimuksista mukainen menetelmä, tunnettu siitä, että keräyspaperia sisältävä massa dispergoidaan painomusteen ja/tai epäpuhtauksi30 en irrottamiseksi massan kuiduista.
- 8. Dispergaattori puukuitumassan, etenkin keräyspaperia sisältävän massan käsittelemiseksi, joka dispergaattori käsittää terillä varustetut vastakkaiset työstöpinnat (2), jotka ovat saatettavissa pyörimisliikkeeseen toistensa suhteen, syöttökanavan (1) massan johtamiseksi teräpintojen väliseen terärakoon sekä poistokammion (6) dispergoidun massan poistamiseksi, tunnettu siitä, että sen teräpinnat (2) ovat kartiomaiset ja että se käsittää lisäksi teräraon poistopäähän sijoitetun juoksupyörän (3).

- 9. Patenttivaatimuksen 8 mukainen dispergaattori, tunnettu siitä, että se käsittää yhden tai useamman laimennusnesteen syöttökanavan (7).
- 10. Patenttivaatimuksen 8 tai 9 mukainen dispergaattori, tunnettu siitä, että kartiopinta muodostaa 10-75° kulman kartion akseliin nähden, edullisesti 10-30° kulman kartion akseliin nähden.
 - 11. Jonkin patenttivaatimuksen 8-10 mukainen dispergaattori, tunnettu siitä, että terät (9) on sijoitettu sanotuille kartiopinnoille niin, että ne asettuvat limittäin.
 - 12. Jonkin patenttivaatimuksen 8-11 mukainen dispergaattori, tunnettu siitä, että laitteen teräpinnat muodostuvat toistensa jatkeena olevista lieriö- ja kartiopinnoista.



(57) Tiivistelmä

Keksinnön kohteena on menetelmä ja laite puukuitumassan, etenkin keräyspaperia sisältävän massan, dispergoimiseksi, jossa hienonnettu massa syötetään toistensa suhteen kiertoliikkeeseen saatettujen dispergaattorin teräpintojen (3) väliin. Keksinnölle on tunnusomaista se, että dispergointi tapahtuu kartiopintojen (3) välisessä teräraossa (5), jonka poistopäähän (6) on järjestetty pumppuna toimiva juoksupyörä (7), jolla massa pumpataan keskipakovoiman avulla dispergaattorista ulos. Dispergaattorin sisempi kartio voi toimia roottorina ja ulompi kartio voi toimia staattorina. Massan voidaan lisäksi laimentaa juoksupyörän (7) imupuolelle syötetyllä nesteellä teräraon (5) poistopäässä.

PATENT COOPERATION : ATY



PCT

REC'D 0 3 OCT 2001

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference		See Notific	cation of Transmittal of International			
BP100192/MAK/PKK	FOR FURTHER ACTION	Preliminar	y Examination Report (Form PCT/IPEA/416)			
International application No.	International filing date (day/mo		Priority date (day/month/year)			
PCT/FI00/00804	21.09.2000		21.09.1999			
International Patent Classification (IPC) or	national classification and IPC7		1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -			
B 02 C 7/00, D 21 D 1,	•					
Applicant			· · · · · · · · · · · · · · · · · · ·			
VALMET MECHANICAL PULE	PING OY et al					
This international preliminary exam Authority and is transmitted to the	nination report has been prepared applicant according to Article 36	by this Inter	national Preliminary Examining			
2. This REPORT consists of a total of	f 4 sheets, includi	ng this cover	sheet.			
This report is also accompan	ied by ANNEXES, i.e., sheets of	the description	on, claims and/or drawings which have			
been aniended and are the ba	asis for this report and/or sheets or 607 of the Administrative Instruc	antaining red	tifications made before this Authority			
		tions under th	he PCI).			
These annexes consist of a total of	sheets.					
3. This report contains indications rela	ating to the following items:					
I Basis of the report			•			
II Priority			·			
L	minion with accordance to					
	opinion with regard to novelty, inv	ventive step a	and industrial applicability			
IV Lack of unity of invent						
V Reasoned statement uncitations and explanation	der Article 35(2) with regard to no ons supporting such statement	ovelty, inven	tive step or industrial applicability;			
VI Certain documents cited	d					
VII Certain defects in the in	nternational application					
	the international application		i			
	application					
Date of submission of the demand	Date of c	ompletion of	this report			
19.04.2001	04.09	2001				
Name and mailing address of the IPEA/SE	Authorize	ed officer				
Patent- och registreringsverket Telex Box 5055 17978						
PATOREG-S Wive Asplund/FLV						
Facsimile No. 08-667 72 88 Form PCT/IPEA/409 (cover sheet) (January 1	Telephon		82 25 00			





International application No.

PCT/FI00/00804

I.	Ba	Basis of the report	
1.	Wit	th regard to the elements of the international application:*	•
	\boxtimes	the international application as originally filed	
	Ē	the description:	
•		pages	
İ		pages	, as originally filed
			, filed with the demand
		pages , filed with the letter of the claims:	
		nages	
			, as originally filed
		, as afficied (together with any	
		pages, filed with the letter of	, filed with the demand
	\Box	the drawings:	
	_		
		nages	, as originally filed
		pages, filed with the letter of	, filed with the demand
		the sequence listing part of the description:	

		pages	, as originally filed
		pages, filed with the letter of	, filed with the demand
T]]	These	the language of a translation furnished for the purposes of international search (under Rule 23.1(b)). the language of the translation of the international application of the international application (under Rule 48.3(b)). the language of the translation furnished for the purposes of international preliminary examination or 55.3).	which is: b)). n (under Rules 55.2 and/
3. W		regard to any nucleotide and/or amino acid sequence disclosed in the international application, the minary examination was carried out on the basis of the sequence listing: contained in the international application in written form.	ne international
ř	_	filed together with the international application in computer readable form.	
ř			
Ļ		furnished subsequently to this Authority in written form.	
Ļ	╣.	furnished subsequently to this Authority in computer readable form.	
		The statement that the subsequently furnished written sequence listing does not go beyond the discinternational application as filed has been furnished. The statement that the information recorded in computer readable form is identical to the written sbeen furnished.	closure in the equence listing has
4.] :	The amendments have resulted in the cancellation of:	
	[the description, pages	
	Ì		
	ľ	the claims, Nos.	
	Ł	the drawings, sheet/fig	
5.		This report has been established as if (some of) the amendments had not been made, since they have beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2 (c)).**	
* Re in an	eplac this i ad 70.	cement sheets which have been furnished to the receiving Office in response to an invitation under s report as "originally filed" and are annexed to this report since they do not contain amendments (0.17).	Article 14 are referred to Rules 70.16
Ar	ıy rep	eplacement sheet containing such amendments must be referred to under item I and annexed to this	report.
D	Om a		4 ' - "



Interr

International application No.

PCT/FI00/00804

V.	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability;
	citations and explanations supporting such statement

1.	Statement			
	Novelty (N)	Claims Claims	1-12	YES NO
	Inventive step (IS)	Claims Claims	1-12	YES NO
	Industrial applicability (IA)	Claims Claims	1-12	YES NO

2. Citations and explanations (Rule 70.7)

The documents cited in the International Search Report represent the prior art. The claimed invention stated in claims 1-12 is not considered to be anticipated by these documents. None of the documents or any relevant combination of them reveal a method or a device for dispersing pulp with a running wheel acting as pump arranged at the outlet end of a narrow opening between conical surfaces, where the dispersing event takes place as described by these claims.

According to the arguments stated above, the invention claimed in claim 1-12 is novel, considered to involve an inventive step and have industrial applicability.



International application No.

PCT/FI00/00804


VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:

On line 7 in claim 1 the word "blade" must be added between "conical" and "surface".

In claim 8, line 38, the reference sign "3" must be changed to "7". In claim 9, line 2, "7" must be changed to "10" and in claim 11, line 9, "9" must be changed to "4".

Form PCT/IPEA/409 (Box VII) (January 1998)



International application No.

PCT/FI 00/00804

Г					00804						
	A. CLASSIFICATION OF SUBJECT MATTER										
	IPC7:	IPC7: B02C 7/00, D21D 1/30 According to International Patent Classification (IPC) or to both national classification and IPC									
L	B. FIEL	DS SEARCHED									
	Minimum										
-	IPC7:										
		ation searched other than minimum documentation to	the extent that such docum	ents are included i	n the fields searched						
-		FI,NO classes as above									
	Electronic (data base consulted during the international search (na	ume of data base and, where	practicable, search	h terms used)						
L		i i									
1	C. DOCU	JMENTS CONSIDERED TO BE RELEVAN	г								
1.0	Category*	Citation of document, with indication, where	appropriate, of the releva	ant passages	Relevant to claim No.						
	A	SE 441758 B (SUNDS DEFIBRATOR (04.11.85), page 1, line 3 figure 1	AB), 4 November 6 - page 2, line	1985 11,	1,8						
		<u></u> ·									
	A	EP 0931584 A1 (VOITH SULZER PA GMBH), 28 July 1999 (28.07 line 5 - line 37, figure 1	NT T	1,8							
1											
	i										
			·								
	Ī	(j							
 -			· · · · · · · · · · · · · · · · · · ·								
	1 Furthe	r documents are listed in the continuation of Bo	x C. X See pate	nt family annex.							
-^	documen	rategories of cited documents of defining the general state of the art which is not considered particular relevance	wife wife life life (f)	HILL WITH THE SERVICE	national filing date or priority tion but cited to understand						
"E	documen	t which may throw doubts on property daim(s) on which is	1 "X" document of partic considered novel or	ular relevance: the cl.	aimed invention cannot he d to involve an inventive						
.0.	abecan te	eason (as specified)	"Y" document of partic	ment is taken alone that relevances the el-	aimed invention councils.						
-p-	document	t referring to an oral disclosure, use, exhibition or other t published prior to the international filing date but later than	combined with one	ve an inventive eten t	when the document is						
Da	Gie partira	ty date claimed actual completion of the international search	"&" document member of	of the same patent far	mily						
		, scarci	Date of mailing of the		orch report						
27	7 Decem	ber 2000	0.5	mai							
		nailing address of the ISA atent Office	Authorized officer								
Во	× 5055, S	S-102 42 STOCKHOLM	Mius As=7 1/m	v							
	Facsimile No. + 46 8 666 02 86										
Fac		2. +46 8 666 02 86 (210 (second sheet) (July 1998)			ł						

HONAL SEARCH REPORT

Information on patent family members

International application No.

04/12/00 | PCT/FI 00/00804

	nt document search report		Publication date		Patent family member(s)	Publicatio date
SE	441758	В	04/11/85	AU	3934985 A	01/11/85
				DE	207937 T	
				EP	0207937 A	
				FI	863998 A	
				JP	61501715 T	
				NO	854832 A	
				NZ	211324 A	
				SE	8401846 D	
				MO	8504433 A	
EP	0931584	A1	28/07/99	DE	19802260 A	29/07/99

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 29 March 2001 (29.03.2001)

(10) International Publication Number WO 01/21312 A1

(51) International Patent Classification7: D21D 1/30

B02C 7/00.

(74) Agent: BERGGREN OY AB; P.O. Box 16, FIN-00101

(21) International Application Number:

PCT/FI00/00804

(22) International Filing Date:

21 September 2000 (21.09.2000)

(25) Filing Language:

Finnish

(26) Publication Language:

English

(30) Priority Data:

19992010

21 September 1999 (21.09.1999)

(71) Applicant (for all designated States except US): VALMET MECHANICAL PULPING OY [FI/FI]; P.O. Box 125, FIN-37601 Valkeakoski (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KANKAANPÄÄ, Veikko [FI/FI]; Rengastie 24 B, FIN-37600 Valkeakoski Helsinki (FI).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,

AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE FOR PROCESSING PULP



(57) Abstract: The object of the invention is a method and a device for dispersing pulp, especially pulp containing waste paper, in which method ground pulp mass is fed between the blade surfaces (3) of a dispersing device that are brought in a rotating movement in relation to one another. The invention is characterized in that the dispersing event takes place in a narrow opening (5) between the conical surfaces (3) at the outlet end (6) of which there is arranged a running wheel (7) acting as pump by which the pulp is pumped out of the dispersing device by centrifugal force. The inner cone of the dispersing device may act as rotor and the outer cone may act as stator. In addition, the pulp may be diluted at the outlet end of the blade opening (5) with fluid introduced to the intake side of the running wheel (7).

WO 01/21312 PCT/FI00/00804

Method and Device for Processing Pulp

5

25

The object of this invention is a method for dispersing pulp, especially pulp containing waste paper, that contains solid material and a liquid phase in which method ground pulp mass is fed between the blade surfaces of a dispersing device that are brought in a rotating movement in relation to one another. An object of the invention is also a dispersing device for applying the aforementioned method.

10 Pulp is treated in a dispersing device where the impurities of the pulp are separated from the fibers that are nevertheless not damaged in the treatment. This may be accomplished with the aid of mutually opposed blade equipped blade surfaces of the dispersing device of which blade surfaces one along with its base (stator) is fixed and the other blade surface along with its base (rotor) is rotating in relation to the other blade surface. The blades and the narrow openings between them cause the pulp move back and forth in the dispersing device, whereby separation of impurities from the fibers is accomplished. The purpose of dispersing is usually mechanical release of impurities from the fibers and simultaneously the grinding of impurities into smaller particles without nevertheless negatively affecting the properties of the fibers.

A dispersing device especially well suited for treatment of pulp mass containing waste paper that contains ink particles or impurities such as adhesives and melt or fusion coatings. A method and dispersing device intended to treatment of this kind of pulp is presented in Patent Publication SE 502 906. In the publication there is presented a grinding element that consists of two mutually opposed grinding disks that are equipped with elevated indents. The inclined elevated patterns are arranged radially on the disks.

In addition to the planar dispersing devices even cone-shaped dispersing devices may be used. However, the problem with the conical dispersing devices is the small amount of mass transferring power allowed by them. Therefore when the pressure in the outlet chamber is high, that is, in the openings between the indents the thrust is high, adjusting the working faces becomes more difficult and the load of the dispersing device increases. The dispersing device may even become clogged, whereby the process is interrupted. This problem is avoided by using the inventive method.

WO 01/21312

PCT/F100/00804

2

In the method according to the invention pulp, especially pulp containing waste paper, is dispersed in a blade opening between cone-shaped surfaces to the outlet end of which is arranged a running wheel acting as a pump by which the pulp is pumped with the aid of centrifugal force out of the dispersing device.

5

10

15

20

25

30

In the method according to the invention a conical dispersing device is used, the advantage of which is a wide working area. Hereby the outer cone preferably acts as stator and the inner cone preferably acts as rotor, onto which is additionally fixed a running wheel. The running wheel is most suitably fixed onto the cone acting as rotor such that it diverts the flow of mass away from the axis of the cone. Most preferably the running wheel is perpendicular to the axis of the cone such that the flow is in a perpendicular plane with regard to the axis. The advantage of a conical dispersing device in regard to a planar dispersing device lies in that blade surface area may be raised 50-150% in relation to a planar dispersing device, whereby the probability of the blade meeting an impurity increases considerably and the efficiency of the dispersing event is improved.

In the method according to the invention the function of the blade surfaces of the dispersing device may be adjusted and regulated by decreasing the pressure in the outlet area of the dispersing device, that is the outlet pressure of the device. The outlet pressure of the dispersing device may be adjusted lower than the pressure in the outlet chamber of the dispersing device by connecting a running wheel onto the rotor of the dispersing device. It is possible to decrease the outlet pressure to such a low value that the pressure at the end of the blade area is lower than in the beginning of the blade area, where by suction is created towards the end area, whereby problems arising due to the low transferring power of the traditional cone-shaped dispersing device are avoided. When using the inventive method the probability of clogging of the dispersing device is thus low. From the above it follows even that when using the inventive method the blades of the working surfaces of the dispersing device may be mounted at closer distances to one another, whereby the number of the blades is increased, whereby further the efficiency and productivity of the dispersing event are improved.

35

In the inventive method the pressure at the inlet of the blade area, that is the inlet pressure, may be even considerably lower than the pressure in the outlet chamber of the dispersing device, into which the running wheel pumps the pulp. Hereby the pressure in the outlet chamber may be raised to such a high level that the pulp once dispersed may be transferred through the piping and to an even higher level than the

20

dispersing device without a separate pump. In this way the inventive method can replace a method, in which a combination of a dispersing device, a pump, a feed tank for the pump and in some cases a screw conveyor is used. Further by the method according to the invention a high efficiency and productivity of the dispersing device are accomplished along with transfer of the pulp to the next stage of the process as well as if need may be, a hydrostatic pressure of the pulp that is sufficiently high for the next stage of the process. Thus the inventive method has a lower energy consumption than traditional methods.

The hydrostatic pressure for pumping of the pulp further to the next piping can be produced with the dispersing device or with a separate pumping equipment. Pumping in the outlet area of the dispersing device is accomplished with the aid of a running wheel situated at the outlet end of the blade opening and of which there may be several in the device. In the method dispersing and pumping are thus realized in separate parts of the device, whereby they don't interfere with each other.

In the method according to the invention pulp may be in addition diluted at the outlet end of the blade opening with fluid introduced to the intake side of the running wheel. Thus the pulp may be diluted for the next process, if need may be, without a separate work stage. In the outlet chamber mixing is sufficient to cause efficient dilution without a separate mixing means. The dilution fluid that may be pressurized or not, is introduced to the intake side of the running wheel through a feed channel of which there is at least one in the device.

- Also, an object of the invention is a dispersing device for dispersing pulp, especially pulp containing waste paper, that contains solid material and a liquid phase. The dispersing device according to the invention comprises mutually opposed conical surfaces equipped with blades which may be brought in a rotating movement in relation to one another, an inlet channel for introducing pulp into the blade opening between the rotating surfaces as well as an outlet chamber for removal of the dispersed pulp. The dispersing device is characterized in that its blade surfaces are conical and that it comprises in addition a running wheel situated at the outlet end of the blade opening.
- As stated above, according to the invention a conical dispersing device is used as dispersing equipment, the advantage of which is a wide working area. Hereby the outer cone preferably acts as stator and the inner cone preferably acts as rotor, onto which is additionally fixed a running wheel: The running wheel is most suitably

10

15

20

25

30

fixed onto the cone acting as rotor such that it diverts the flow of mass away from the axis of the cone. The advantage of a conical dispersing device in regard to a planar dispersing device lies in that the number of blades may be raised 50-150% in relation to a planar dispersing device, whereby the probability of the blade meeting an impurity increases considerably and the efficiency of the dispersing event is improved.

Further in addition to the above, the following advantages among others are realized by a conical dispersing device: in dispersing impurities higher efficiency than with a planar dispersing device is realized by the same known energy level; breaking of pulp fibers is reduced because energy is distributed on a greater number of blades, whereby a higher energy level than with a planar dispersing device may be used without nevertheless damaging the fibers; the service life of the blades of the dispersing device is increased because the working surface area is larger and hence the relation energy/blade lower.

The blade surfaces of a conical dispersing device may be at an angle of 10-75° in relation to the axis of the cone, preferably at an angle of 10-30° in relation to the axis of the cone. The blade surfaces may also consist of cylindrical surfaces and conical surfaces that are in extension to one another, however, it is preferred that the blades are mainly situated on conical surfaces. The blades are arranged on the moving blade surface (rotor) and on the fixed blade surface (stator) such that the blades are overlapping one another. The shape of the blades may be chosen at will, but their size must be such that the rotor and the stator form a pair in which the blades overlap.

The flow channels of the running wheel are designed such that the pressure increases towards the outer circumference of the running wheel (cf. a centrifugal pump). A high pressure in the flow channels and at their outlet openings stops the pulp from flowing back from the outlet chamber to the blade area. Between the running wheel and the outlet chamber wall there is a narrow opening that makes it possible for the running wheel to move freely but not for the pulp to flow back or for the pressure to drop in the outlet chamber.

35 The invention is explained more in detail in the following with regard to the appended drawings in which:

Fig. 1 presents an embodiment of the dispersing device according to the invention, Fig. 1 is a partial longitudinal section of the aforementioned dispersing device,

Fig. 2 presents a partial scheme of the structure and flow channels of the running wheel of the dispersing device presented in Fig. 1. Fig. 2 shows in addition the principle of the flow channels of the running wheel. The partial scheme is a cross section of the plane marked AA in Fig. 1, and

Fig. 3 presents the structure of the blade surface of the dispersing device according to Fig. 1.

The conical dispersing device presented in Fig. 1 consists of a body part, a cone that includes the conical surfaces, of a running wheel and of an outlet chamber. The components in Fig. 1 are: 1 a feed point; 2 a cone; 3 conical surfaces; 4 a blade; 5 a blade opening; 6 an outlet point; 7 a running wheel; 8 a flow channel of the running wheel; 9 an outlet chamber; 10 a feed channel of the dilution fluid; 11 a narrow opening.

The pulp that contains waste paper and the density of which is suitably 15-35%, is introduced to the conical dispersing device at the feed point 1. The pulp moves back and forth on the conical surfaces 3 in the narrow openings 5 of the blades 4 while it is simultaneously transferred forwards on the cone 2. The negative pressure created at the outlet point 6 of the blade area increases the mobility of the pulp forwards towards the outlet point 6. In the blade area impurities of the pulp are separated mechanically from the fibers of the pulp, in addition to which the impurities are ground into smaller particles.

25

30

20

As the pulp moves on to the outlet point 6 of the blade area it is blended with the dilution fluid that is introduced to the outlet point 6 through a feed channel 10 for the dilution fluid. The dilution fluid may be pressurized or not. As the running wheel 7 revolves a flow is created and the pulp is blended in the dilution fluid. The revolving motion also accomplishes the differing pressures between various parts of the device mentioned above. The diluted pulp is transferred through flow channels 8 of the running wheel according to the principle presented in Fig. 2 to the outlet chamber 9. In the outlet chamber 9 the density of the pulp is suitably 4-12%.

In Fig. 2 is presented a partial scheme of the structure of the running wheel 7 and of the flow channels 8 as well as the principle of the flow channels 8 of the running wheel. The partial scheme is a cross section of the plane marked AA in Fig. 1. The running wheel 7 has flow channels 8 that protrude axially outwards and are outlined

by organs 12. The flow of pulp 13 is away from the axis of the running wheel 7 in a direction opposite to the direction of rotation 14 of the running wheel 7. The running wheel 7 is mounted on the rotor in such a way that the direction of the flow of mass 13 changes in relation to the axis of the cone.

Between the running wheel 7 and the wall of the outlet chamber 9 there is a narrow opening 11 that makes it possible for the running wheel 7 to move freely but not for the pulp to flow backwards or for the pressure to decrease in the outlet chamber.

- In Fig. 3 is presented the arrangement of the blades 4 on the conical surface 3. The blades may be parallel with the conical surface lines or at a certain angle thereto, and their shape and mutual distance may be varied at will, as may be the blade patterns in various zones.
- To the one skilled in the art it is obvious that the inventive method and the inventive device for dispersing pulp are not limited to the example presented above while they are based on the following claims.

Claims

1. A method for dispersing pulp, especially pulp containing waste paper, that contains solid material and a liquid phase, in which method ground pulp mass is fed between the blade surfaces (3) of a dispersing device that are brought in a rotating movement in relation to one another, characterized in that the dispersing event takes place in a narrow opening (5) between the conical surfaces (3), at the outlet end (6) of which there is arranged a running wheel (7) acting as pump by which the pulp is pumped out of the dispersing device by centrifugal force.

10

20

5

- 2. A method according to claim 1, characterized in that the inner cone of the dispersing device acts as rotor and the outer cone acts as stator.
- 3. A method according to one of the preceding claims, characterized in that said running wheel (7) is fixed on the cone acting as rotor in such a way that it diverts the flow of mass away from the axis of the cone.
 - 4. A method according to one of the preceding claims, characterized in that the dilution of pulp at the outlet end (6) of the blade opening (5) is accomplished by fluid introduced to the intake side of the running wheel (7).
 - 5. A method according to claim 4, characterized in that the density of the pulp to be dispersed is before dilution 15-35%.
- 25 6. A method according to claim 4 or claim 5, characterized in that the density of the pulp is after dilution 4-12%.
- 7. A method according to one of the preceding claims, characterized in that the pulp containing waste paper is dispersed in order to release printing ink and/or impurities from the fibers of the pulp.
- 8. A dispersing device for processing pulp, especially pulp containing waste paper, the dispersing device comprising mutually opposed working surfaces (2) fitted with blades that may be brought into a revolving motion in relation to one another, a feed channel (1) for introducing pulp to the blade opening between the blade surfaces as well as an outlet chamber (6) for removal of the dispersed pulp, characterized in that its blade surfaces (2) are conical and that it comprises additionally a running wheel (3) situated at the outlet end of the blade opening.

10

- 9. A dispersing device according to claim 8, characterized in that it comprises one or more feed channels (7) for the diluting fluid.
- 10. A dispersing device according to claim 8 or claim 9, characterized in that the conical surface is at a 10-75° angle to the axis of the cone, preferably at a 10-30° angle to the axis of the cone.
 - 11. A dispersing device according to one of claims 8 10, characterized in that the blades (9) are arranged on said conical surfaces such that they overlap.
 - 12. A dispersing device according to one of claims 8 11, characterized in that the blade surfaces of the device consist of cylindrical surfaces and conical surfaces that are in extension to one another.




Fig.1




Fig.2




Fig. 3



International application No.

PCT/FI 00/00804

A. CLASSIFICATION OF SUBJECT MATTER IPC7: B02C 7/00, D21D 1/30 According to International Patent Classification (IPC) or to both national classification and IPC FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC7: B02C, D21B, D21D Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched SE,DK,FI,NO classes as above Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Category* Citation of document, with indication, where appropriate, of the relevant passages Relevant to claim No. A SE 441758 B (SUNDS DEFIBRATOR AB), 4 November 1985 1,8 (04.11.85), page 1, line 36 - page 2, line 11, figure 1 A EP 0931584 A1 (VOITH SULZER PAPIERTECHNIK PATENT 1,8 GMBH), 28 July 1999 (28.07.99), column 3, line 5 - line 37, figure 1 Further documents are listed in the continuation of Box C. See patent family annex. Special categories of cited documents: later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention document defining the general state of the art which is not considered to be of particular relevance earlier application or patent but published on or after the international "X" document of particular relevance: the claimed invention cannot be filing date considered novel or cannot be considered to involve an inventive document which may throw doubts on priority claim(s) or which is step when the document is taken alone cited to establish the publication date of another citation or other special reason (as specified) document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination document referring to an oral disclosure, use, exhibition or other means being obvious to a person skilled in the art document published prior to the international filing date but later than the priority date claimed "&" document member of the same patent family Date of the actual completion of the international search Date of mailing of the international search report 0 9 -01- **2001** <u> 27 December 2000</u> Name and mailing address of the ISA/ Authorized officer **Swedish Patent Office** Box 5055, S-102 42 STOCKHOLM Wiva Asplund/ELY Facsimile No. + 46 8 666 02 86 Telephone No. +46 8 782 25 00



International application No.

04/12/00

PCT/FI 00/00804

Patent document cited in search report			Publication date	Patent family member(s)		Publication date	
SE	441758	В	04/11/85	AU	3934985 A	01/11/85	
				DE EP	207937 T 0207937 A	30/04/87	
				FI	863998 A	14/01/87 02/10/86	
				JP	61501715 T	14/08/86	
				NO	854832 A	02/12/85	
				NZ	211324 A	11/07/86	
				SE	8401846 D	00/00/00	
				MO	8504433 A	10/10/85	
EP	0931584	A1	28/07/99	DE	19802260 A	29/07/99	

Form PCT/ISA/210 (patent family annex) (July 1998)

PATENTTI- JA REKISTERIHALLITUS

Patentti- ja innovaatiolin

TUTKIMUSRAPORTTI
10/088539

HAKEMUSNUMERO	LUOKITUS IPC7	JC10 Rec'd POT/P10 9 MAR 2002
19992010	D21D1/.26,	802 (2/08
		🔘 jatkuu kääntöpuolella

Patenttivirast FI, SE, NO, DK	ojen julkaisut , DE, CH, EP, WO, GB, US:	
0211	1/00-1/40, BOZCR,7	

		uu kääntöpuolella
Muu aineisto		a de f
Lasik	irjoja, khtiartikkeleja, esitteitä	
Tietal	Konehaku EPOQUE VV-75-2000	***************************************
· ICIOR	onehaku Cdrom (RV), (AV), vv96990 jatko	u kāāntōpuolella
VIITEJULKAI	SUT	,
Kategoria*)	Julkaisun tunnistetiedot	Koskee vaatimuksia
Ą	EP A 886001 02101/30	
A	EP A 922495 B02C7/12	***************************************
Y	Wachard Lit 1. 1071	***************************************
A	Wochenblatt 1:1976, pp3-37 bellwood Machinery, Nassjo,	6
	Sweden Krima Disperser Type	•••••••••••••••••••••••••••••••••••••••
	KD KD	
	□ jatkut	ı kääntöpuolella
Y Patento ja yksi ta	itavuuden kannalta merkittävä julkaisu yksinään tarkasteltuna itavuuden kannalta merkittävä julkaisu, kun otetaan huomioon tämä ii useampi-samaan kategoriaan kuuluva julkaisu ekniikan tasoa edustava julkaisu, ei kuitenkaan patentoitavuuden este	
Paiväys 2,6,20	Tutkija Juliso Suhol	